



3055

- 50 hp, 4 cylinders engine
- 12F+12R transmission
- Hydraulic PTO 540/1000 rpm
- Tractor mother regulation (tmr) compliant
- Rear differential lock



TECHNICAL DATA

ENGINE		
Type		Direct injection diesel
Power rating	HP/kW	50/36,8
N°Cylinders	n°	4
Swept volume	cc	3168
TRANSMISSION		
N° Speeds		12 + 12 synchro shift with mechanical drive and four-wheel drive
Reverse Shuttle		Mechanical, synchronized
Speed	kph	40
HYDRAULIC CIRCUIT		
Pump flow rate	l/min	15 + 45
Rear hydraulic control valves		2 SE/DE
DRIVER'S AREA		
Platform		Integral platform on liquid sylicon silent block
WEIGHTS AND DIMENSIONS		
Length	mm	4136
Width	mm	1660
Wheelbase	mm	1990
Weight with safety frame	kg	2300
Weight with cab	kg	2480
TYRES		
Front - Rear	8.3-20	14.9-24
	8.3-20	12.4-28
	260/70R20	380/85R24
	280/70R16	260/70R20
	260/70R20	380/85R24
	31X9.5-16	13-20
	280/70 R20	380/70 R28

COMPACT, EFFICIENT AND RELIABLE

In compliance with the new TMR norm, thanks to the evolution of modern machinery, the new ARBOS 3055 offers reliability, quality and performance. Environment-friendly 50 horsepower engine, hydraulic PTO (540/1000rpm), rear differential lock, and 24 speeds, ARBOS combines efficiency and utility in a carefully designed machine that has just about everything you expect, and even more.

